HBH750 Series
Eclipse™
High-Performance Blender

UNIQUE FEATURES

Eclipse® Blender

QuietBlend™ Technology - Greatly reduces motor noise and works with the advanced Quiet Shield™ enclosure to lower sound to conversation level.

Compact Size - Blender width of 8.5″ / 22cm fits neatly on top of counter. The Quiet Shield™ enclosure opens to a maximum height of just 22″/ 56 cm.

Powerful Motor - 3 peak Hp† motor with a special airflow design that helps prevent motor overheating and helps extend motor life.

Pre-programmed Cycles - Choose from 5 buttons for popular drinks and over 100 additional cycles. Custom programs are available and easily downloaded with a memory card.

Jar Pad Sensor - Turns off motor when container is not in place to reduce grinding and "wear and tear" from operator misuse (120V only).

Quiet Shield™ Sensor - Turns off motor when operator lifts Quiet Shield.™ (can be disabled on 120V .)

Lifetime Warranty on Motor Drive Coupling and Stainless Steel Blade - Ensures that the parts are free from defects in material and workmanship for the life of the part.

Wave~Action® System - Unique container design continually forces mixture down into the blades for a super-creamy drink profile every time.

Overheat Protection - Display alerts operator if motor overheats and provides directions to run a quick cool-down cycle.

† Input power

Converts for in-counter use

Easy-read display and intuitive, one-touch blending functions

Convenient clips allow for easy removal of Quiet Shield™ for cleanup

Quiet Shield™ opens to a max height of only 22 inches/56 cm

Memory card for custom programming

Specifications:

Standard: Unit comes with base, one 48 oz./1.4 L polycarbonate container, Quiet Shield™ sound enclosure

Controls: Touchpad

Motor: 3 peak Hp (input power)

Weight: 15.3 lbs / 6.9 kg (shipping)

Warranty: 2 years or 20,000 cycles

ExpressCare WARRANTY
U.S. ONLY

Global Care

11.25"/28.6 cm

18.5" 47 cm

8.5"/21.6 cm

120V Specifications: 120V~, 60 HZ, 8.6 A
HBH750

c (UL) us   NSF.

230V Specifications:
HBH750-CE
HBH750-UK
HBH750-CN

CE   RoHS COMPLIANT

220-240V~, 50-60 HZ, 1000W