

E3840F SINGLE PAN, TWIN BASKET FRYER WITH IN-BUILT FILTRATION





MODELS and ACCESSORIES

E3840F - Single pan fryer with filtration and manual controls

- Fully integrated extended flue
- Side and rear screens c/w draining shelf
- Factory fitted, adjustable castors
- Fixed installation kit
- Suiting kit

KEY FEATURES

- · Integrated filtration as standard
 - extends oil life and reduces running costs
- Drain bucket, strainer and filter supplied as standard
 - No hidden extra cost for these accessories
- Stainless steel hob with mild steel pan
 - robust construction to withstand busy demands
- Temperature range between 130 190°C
 - variable, precise control
- Sediment collection zone
 - keeps oil cleaner for longer
- · Fast-acting safety thermostat
 - peace of mind should oil overheat
- Resting position for elements
 - allows easier, safe cleaning
- Lid supplied as standard
 - protects and extends oil life
- Fish grid supplied as standard
 - keeps cooked portions off pan base
- Large diameter drain valve
 - for simple and efficient pan draining
- · Laser-etched control icons
 - permanent, indelible markings

INSTALLATION NOTES

Adequate ventilation must be provided to supply sufficient fresh air and to allow easy removal of any such products that may present a risk to health. Please consult current legislation for details that relate to specific locations.

Install unit on a level, fireproof surface in a well-lit position. If floor is made of a combustible material, local fire requirements must be checked to ensure compliance.

A clearance of 150mm should be observed between appliance and any combustible wall.










E3840F SINGLE PAN, TWIN BASKET FRYER WITH IN-BUILT FILTRATION

MODEL DIMENSIONS (in mm)







SPECIFICATION DETAILS

E3840F	•
--------	---

Electrical rating (kW) 20

Electrical supply voltage 400V 3N~

Required electrical supply

400V 3N~ (amps) 33

Electrical current split (amps) L1: 29 / L2: 29 / L3: 29

Notes:

Oil capacity (litres) 20 * pre-blanched,
Hourly chip output * (kg) 58 chilled 15mm size.
Weight (kg) 77 Recommended load

Weight (kg) 77 Recommended load Packed weight (kg) 83 1.5kg per basket.

