


Opus 800

a natural evolution



Gas Griddles 600mm and 900mm wide

OG8201, OG8201/C, OG8201/R, OG8202, OG8202/C, OG8202/R

- **Maximised cooking area, griddle plates sit flush to the sides of the unit**
- **Left and right independently controlled heat zones for flexibility and economy during quiet periods**
- **Convenient piezo ignition and pilot burners for stand-by operation**
- **Flame failure protection**
- **Half ribbed plate and chrome plate options**



OG8201



OG8202

Griddle Features

- Tubular burner system
- 15mm thick griddle plate
- Maximised cooking area, griddle plates sit flush to the sides of the unit
- Welded splashguard for easy cleaning
- Left and right independently controlled heat zones
- Accurate thermostatic control up to 280°C
- Flame failure protection
- Convenient piezo ignition
- 48mm round aperture grease drain
- Large 2 litre collection drawer

/R Half-ribbed plate option

- For attractive branding presentation marks

/C chrome plate option

- Easy to clean and for reduced heat radiation for a comfortable working environment and reduced energy costs
- Over temperature safety cut out
- Easy access reset button

Cleaning and Servicing

- Easy clean stainless steel external finish
- Welded splashguard for easy cleaning
- Easy clean 48mm round aperture grease drain
- Access to all parts from the front and top of unit

Overall construction

- Permanent laser etched markings on fascia and knobs
- 15mm thick griddle plate
- Top welded sealed plate
- 1.2 mm stainless steel welded bull nose and surround
- 1.2 mm stainless steel base panel
- 1.2 mm stainless steel side panels
- Welded stainless steel debris collection drawer
- Supplied on 150mm legs in compliance with CE legislation
- Sits flush to the wall, recess for services

Inclusive Accessories

- Scraper (not for chrome models)

Available Options

- / N Natural Gas or /P Propane Gas
- /R Half-ribbed plate
- /C Chrome plate

Available Accessories

- Scraper (not for chrome models)
- OA8972 Pedestal with doors for units 600mm wide
- OA8917 Floor stand for units 600mm wide
- OA8973 Pedestal with doors for units 900mm wide
- OA8914 Floor stand for units 900mm wide
- LK10 short leg kit

Opus 800

a natural evolution

Technical Data

	OG8201	OG8202
With chrome plate	OG8201/C	OG8202/C
With half-ribbed plate	OG8201/R	OG8202/R
Width (mm)	600	900
Depth (mm)	800	800
Overall height (mm)	535	535
Height to hob (mm)	400	400
Cooking area w x d (mm)	590 x 500	890 x 500
Number of individually controlled heat zones	2	2
Heat input per burner (kW)	7.75 natural, 7.75 propane	11.5 natural, 11.5 propane
Total heat input at full rate (kW)	15.5 natural, 15.5 propane	23 natural, 23 propane
Total heat input at full rate (Btu per hour)	52,888	78,479
Gas consumption at full rate Natural (m ³ h ⁻¹)	1.48	2.19
Gas consumption at full rate Propane (kg h ⁻¹)	1.11	1.64
Gas pressure (mbar)	20 natural, 37 propane	20 natural, 37 propane
Gas connection (BSP)	½"	½"
Net weight (kg)	87	96
Packed weight (kg)	96	130
Shipping volume (m ³)	0.6	0.8

OG8201

OG8202/R

