

## HJC4-SA TECHNICAL DATA

| Dimensions (mm)                | HJC4-SA                     |
|--------------------------------|-----------------------------|
| Finish (Ext/Int)               | Stainless Steel / Aluminium |
| Width (Ext/Int)                | 2360/1830                   |
| Depth (Ext/Int)                | 700/585                     |
| Height (Ext/ <i>Int</i> )      | 857/600                     |
| Door Opening                   | 390                         |
| Capacity cu.ft/ltrs            | 25.3/715                    |
| Temperature (°C)               | +1/+4°C                     |
| Climate Class                  | Class 4 (30°C)              |
| Power Supply                   | 230V/50Hz/1Ph               |
| Fuse (Amps)                    | 13                          |
| Defrost                        | Automatic Off Cycle         |
| Noise level (dBA)              | 63                          |
| Fittings                       |                             |
| Shelves                        | 8                           |
| Trayslides per door            | 4                           |
| Electrical / Energy Data       |                             |
| Refrigerant                    | R290                        |
| Energy Efficiency Class        | В                           |
| Energy Consumption (kW / 24hrs | 5) 2.60                     |
| Start Up (Amps)                | 9.5                         |
| Running (Amps)                 | 1.68                        |
| Heat Rejection                 | 484                         |



## **Key Features**

- Radiused, easy clean, interior based corners
- Self closing doors
- Barrel locked doors
- Magnetic balloon door gaskets
- Anti-tilt trayslides
- Removable racking system
- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential).
- Heavy duty, non-marking swivel castors with brakes
- Removable refrigeration system designed for easy service and maintenance
- CoolSmart controller

- · Designed and engineered to operate efficiently up to a 43°C
- Fully automatic air cooled condensing unit
- · Defrost water is vaporised using recycled heat from compressor
- High performance helium leak testing

## **Options**

- Stainless steel interior
- Additional shelving / trayslides
- Drawer banks (2 or 3)
- Raised pan holder
- Screw on splash-back
- Adjustable legs in lieu of castors (add 10mm to height)
- Wells full / standard / special

## **IMPORTANT NOTES:**

\*Energy consumption is tested to EN16825 in 24hrs

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

\*\*Heat rejection is evaporating at -10°C in 32°C Ambient

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration Bryggen Road, North Lynn Industrial Estate King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000 Spares: +44(0) 1553 817 017 E info@williams-refrigeration.co.uk W www.williams-refrigeration.co.uk





