



HA400-SA TECHNICAL DATA

Dimensions (mm)	HA400-SA
Finish (Ext/Int)	Stainless Steel / Aluminium
Width (Ext/Int)	695/545
Depth (Ext/Int)	684/477
Height (Ext/Int)	1896/1315
Door Opening	545
Capacity cu.ft/ltrs	14.5/410
Temperature (°C)	+1/+4°C
Climate Class	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph
Fuse (Amps)	13
Defrost	Automatic Off Cycle
Noise level (dBA)	59

Fittings

Shelves	3
Trayslides per door	-

Electrical / Energy Data

Refrigerant	R290
Energy Efficiency Class	D
Energy Consumption (kW / 24hrs)	2.15
Start Up (Amps)	9.5
Running (Amps)	1.33
Heat Rejection	484



Key Features

- Stainless steel exterior with aluminium interior
- Barrel locked doors
- Self closing doors
- Magnetic balloon door gaskets
- Removable racking system
- Precision injected, high density polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential).
- CoolSmart controller
- Designed and engineered to operate efficiently up to 32°C ambient
- Air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor

- High performance helium leak testing

Options

- 50mm castors
- Left hand hung door
- Interior light
- Additional shelves / clips

IMPORTANT NOTES:

*Energy consumption is tested to EN16825in 24hrs

**Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

