www.williams-refrigeration.co.uk

BC2-SS TECHNICAL DATA

Dimensions (mm)	BC2-SS
Finish (Ext/*Int*)	Stainless Steel / *Stainless Steel*
Width (Ext/*Int per section*)	900/*377*
Depth (Ext/*Int*)	530/*378max 253min*
Height (Ext/*Int*)	903/*745*
Door Opening	1130
Capacity 330ml bottles	184
Temperature (°C)	+4/+10°C
Power Supply	230V/50Hz/1Ph
Fuse (Amps)	13
Defrost	Auto defrost and evaporation

Fittings	
Shelves	4

Electrical / Energy Data - R134A Refrigerant	
Refrigerant	R134A
Energy Efficiency Class	C
Energy Consumption (kW / 24hrs)	2.83
Start Up (Amps)	8
Running (Amps)	2
Heat Rejection	283

Key Features

- Choice of exterior finishes - black PVC coated galvanised steel or stainless steel
- Hard wearing exterior with hygienic, easy to clean mirrored stainless steel interior
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 32°C ambient.
- Precision injected, high density 35mm polyurethane insulation
- Castors to rear, adjustable feet to front
- Barrel locked doors
- Double glazed doors and bright, low energy consumption lighting
- Fully adjustable nylon coated wire shelves to suit stacking requirements

Options

- Solid doors (available in stainless steel and black finish)
- Wine shelves

IMPORTANT NOTES:

*Energy consumption is tested to BS EN16902:2016

**Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk