

BC3-SS TECHNICAL DATA

Dimensions (mm)	BC3-SS
Finish (Ext/Int)	Stainless Steel / Stainless Steel
Width (Ext/Int per section)	1352/377
Depth (Ext/Int)	530/378max 253min
Height (Ext/ <i>Int</i>)	903/745
Door Opening	1130
Capacity 330ml bottles	294
Temperature (°C)	+4/+10°C
Power Supply	230V/50Hz/1Ph
Fuse (Amps)	13
Defrost	Auto defrost and evaporation
Fittings	
Shelves	6
Electrical / Energy Data -	R134A Refrigerant
Refrigerant	R134A
Energy Efficiency Class	Е



Key Features

6.04

10.3

2.4

534

- Choice of exterior finishes black PVC coated galvanised steel or stainless steel
- Hard wearing exterior with hygienic, easy to clean mirrored stainless steel interior
- CoolSmart controller
- Designed and engineered to operate efficiently up to a 32°C ambient.
- Precision injected, high density 35mm polyurethane insulation
- · Castors to rear, adjustable feet to front
- Barrel locked doors
- Double glazed doors and bright, low energy consumption lighting

· Fully adjustable nylon coated wire shelves to suit stacking requirements

Options

- Solid doors (available in stainless steel and black finish)
- · Wine shelves

IMPORTANT NOTES:

Energy Consumption (kW / 24hrs)

Start Up (Amps)

Running (Amps)

Heat Rejection

*Energy consumption is tested to BS EN16902:2016

**Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance.

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration Bryggen Road, North Lynn Industrial Estate King's Lynn, Norfolk. PE30 2HZ T +44(0) 1553 817 000 Spares: +44(0) 1553 817 017 E info@williams-refrigeration.co.uk W www.williams-refrigeration.co.uk





