



HJ500U TECHNICAL DATA

Dimensions (mm)	HJ500U
Finish (Ext/Int)	Stainless Steel / Stainless Steel
Width (Ext/Int)	727/567
Depth (Ext/Int)	837/660
Height (Ext/Int)	1940/1332
Door Opening	567
Capacity cu.ft/ltrs	18.5/523
Temperature (°C)	+1/+4°C
Climate Class	Class 4 (30°C)
Power Supply	230V/50Hz/1Ph
Fuse (Amps)	13
Defrost	Automatic Off Cycle
Noise level (dBA)	63

Fittings

Shelves	3
Trayslides per door	6

Electrical / Energy Data - R134a Refrigerant

Refrigerant	R134A
Energy Efficiency Class	D
Energy Consumption (kW / 24hrs)	1.90
Start Up (Amps)	9.6
Running (Amps)	1.6
Heat Rejection	407

Electrical / Energy Data - R290 Refrigerant

Refrigerant	R290
Energy Efficiency Class	D
Energy Consumption (kW / 24hrs)	1.91
Start Up (Amps)	9.5
Running (Amps)	1.67
Heat Rejection	484



Key Features

- Full length integral 'easy grab' door handle
- Radiused, easy clean, interior based corners
- Self closing doors
- Barrel locked doors
- Magnetic balloon door gaskets
- Anti-tilt trayslides
- Removable racking system
- Precision injected, high density up to 80mm polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Heavy duty, non-marking swivel castors with brakes
- CoolSmart controller
- Designed and engineered to operate efficiently up to 43°C ambient
- Air cooled condensing unit
- Defrost water is vaporised using recycled heat from compressor
- High performance helium leak testing

Options

- Additional shelving / trayslides
- Left hand door hang
- Adjustable legs in lieu of castors (add 10mm to height)

IMPORTANT NOTES:

*Energy consumption is tested to EN16825 in 24hrs

Allow minimum of 500mm above cabinet for maintenance and ventilation. All refrigeration equipment requires adequate ventilation for efficient and effective performance.

**Heat rejection is evaporating at -10°C in 32°C Ambient

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

