



LWMP523 TECHNICAL DATA

Dimensions (mm)	LWMP523
Finish (Ext/Int)	Stainless Steel / Stainless Steel
Width (Ext/Int)	727/567
Depth (Ext/Int)	837/660
Height (Ext/Int)	1940/1332
Door Opening	567
Capacity cu.ft/ltrs	18.5/523
Temperature (°C)	-18/-22°C
Climate Class	Class 5 (40°C)
Power Supply	230V/50Hz/1Ph
Fuse (Amps)	13
Defrost	Automatic Electric
Noise level (dBA)	61

Fittings

Shelves	4
---------	---

Electrical / Energy Data - R290 Refrigerant

Refrigerant	R290
Start Up (Amps)	9.5
Running (Amps)	2.59
Heat Rejection	623

Medi+ Controller

- Clear digital display
- Audio and visual hi/lo temp alarm
- Audio and visual door open alarm
- Maximum and minimum temperature memory
- Auto defrost
- Air & evaporator probe
- Lockable keypad
- Precise temperature control using decimal point operation

IMPORTANT NOTES:

Heat rejection is evaporating at -10°C in 32°C Ambient

All refrigeration equipment requires adequate ventilation for efficient and effective performance.



Key Features

- Spark free interior
- Designed and engineered to operate efficiently up to 43°C ambient
- Stainless steel exterior and interior
- Full length integral 'easy grab' door handle
- Self closing doors with barrel locks
- Magnetic balloon door gaskets with 100% tight seal
- White nylon coated wire shelves
- Removable racking system with anti-tilt trayslides
- Heavy duty, non-marking swivel castors with brakes
- Precision injected, high density 80mm polyurethane insulation with low GWP (Global Warming Potential) and zero ODP (Ozone Depletion Potential)
- Defrost water is vaporised using recycled heat from compressor
- Air cooled condensing unit
- High performance helium leak testing

Options

- Punched stainless steel shelves
- Additional shelving
- Left hand door hang
- Mains failure alarm

Williams is committed to a policy of continual product development and innovation. As such, we reserve the right to change product specifications stated without prior notice.

Williams Refrigeration
Bryggen Road,
North Lynn Industrial Estate
King's Lynn, Norfolk. PE30 2HZ

T +44(0) 1553 817 000
Spares: +44(0) 1553 817 017
E info@williams-refrigeration.co.uk
W www.williams-refrigeration.co.uk

